

STABILITY RESEARCH PROGRESS ON HIGH-POWER PULSE MODULATOR FOR SXFEL-UF*

Q.B. Yuan^{1,2†}, Y.F. Liu^{1,2,3}, Y.H. Wu^{1,2}, M. Gu^{1,2}, J. Tong^{1,2,3}

^{1,2}Shanghai Institute of Applied Physics, Chinese Academy of Sciences, Shanghai, China

^{1,2}Shanghai Advanced Research Institute, Chinese Academy of Sciences, Shanghai, China

³also at University of Chinese Academy of Sciences, Beijing, China

Abstract

SXFEL-UF (Shanghai Soft X-ray Free Electron Laser User Facility) under construction presently demands higher energy stability. Stability of pulse modulator feeding power for klystron plays an utmost important role in energy stability and occupy dominant factors in bringing influences in stability of RF power. Currently, stability of high-power pulse modulator of LINAC (Linear Accelerator) is on the level of 0.1% to 0.05% usually. In order to meet the higher stability requirements, it is very necessary for close-loop feedback control techniques instead of traditional open-loop to be applied in the modulator design. The stability controller adopts double control-loops techniques which feedback signals are respectively from PFN (Pulse Forming Network) and pulse transformer in oil tank. In addition, the paper also introduces recent progress on high stable CCPS research (Capacitor Charging Power Supply), which brings direct impact on the stability of modulator. In comparison with the former close-loop design, high stable CCPS design takes the overall modulator stability into full consideration. And the feedback control algorithm utilized to output PWMs (Pulse Width Modulations) for full bridge switches is implemented in the CCPS controller directly rather than modulator controller independent of CCPS. It is expected feasibly to obtain 0.01% stability by taking the above measures.

INTRODUCTION

SXFEL-UF is an X-ray Free Electron Laser (XFEL) User Facility with 1.6 GeV under tense construction [1], which has been developed on the basis of SXFEL-TF(Shanghai Soft X-ray Free Electron Laser Test Facility). In order to obtain more excellent beam quality, microwave system is requested to achieve more stable amplitude stability and more tight tolerances of phase jitter (0.01% rms). Through beam switch yard, SXFEL-UF would transfer beam to one SBP line with ten sets of in-vacuum undulators and another undulator line with two sets of U80s, four sets of U40s, one set of U55, ten sets of U235s and two sets of EPU30s.

However, on the current high power modulator technical condition, it is very difficult and challenging for us to enhance either pulse-to-pulse amplitude stability or ripple within pulse (flatness of flat top) especially to 0.01% level. Thus, whether could LLRF (Low-level RF)

control techniques of microwave system compensate deficiency resulting from unsatisfactory modulator performance? LLRF can accomplish controlling stability of amplitude and phase of RF to some certain level, but which to what extent mostly depends on amplitude stability level of pulsed modulator.

As mentioned in abstract, the performance of the CCPS applied in modulator exactly take up absolutely important factors in modulator's stability [2]. Presently, commercial CCPS products universally adopt analog PWM control techniques and close-loop feedback within internal CCPS. It is not enough for the CCPS only utilizes close-loop with feedback from internal CCPS, feedback from outside CCPS is also indispensable.

This paper would firstly present some current experimental results through adopting close-loop control technology on the basis of routine commercial CCPS. Then recent in-house research progress and design about high repeatable stability are introduced.

STABILITY CONTROL

Stability feedback control adopts three kinds of control routes (Figure 1), which are respectively high precision




Figure 1: Stability feedback control schematic for pulse modulator.

sampling of PFN voltages from HV divider(route A), high precision sampling of pulsed waveform through capacitor networks and differentiated amplifier(route C) and high-speed sampling with multi-datum average of pulsed waveform through capacitor networks and differentiated amplifier (route B) [3].The HV divider is a resistor network with high precision and low temperature drift, which is immersed in a oil cylinder with a ratio 10000:1. The LPF is one 5-order active low pass filter with the cut-off frequency 5kHz. The micro-control unit (based on FPGA) acquires data from the 18-bit A/D (600 kHz sampling rate) and 14-bit high-speed A/D (60 MHz sampling rate) through parallel connections with each other.

* Work supported by the National Natural Science Foundation of China (NO.11675250).

† yuanqibing@zjlab.org.cn

PFN Sampling (Route A)

According to the acquisition datum of voltages of PFN by use of high precision resistor voltage divider, The controller regulates the D/A values through analog control interface between CCPS and FPGA system with the proportional integral (PI) algorithm. In order to draw a comparison between close-loop and open-loop control condition, two kinds of test results are respectively recorded and analysed (Figure 2 and Figure 3). Figure 2 demonstrates PFN voltages would drift under open-loop condition, and the centric values (the red curve) fluctuate 0.01% approximately due to heat drift of distribution parameters of inductance and capacitor.




Figure 2: Open-loop test results of PFN voltages.

The analysis results measured on close-loop feedback control condition is illustrated in Figure 3, which indicates the centric values have no drift and are stabilized in a straight and horizontal line. Meanwhile, Figure 3 also manifests that although feedback control can restrain long-term drift, short-term fluctuation is hard to be accomplished effectively.




Figure 3: Close-loop test results of PFN voltages.

Pulse Waveform Sampling (Route C)

The difference of pulsed waveform sampling control ring from PFN sampling feedback is that feedback signal is gained from capacitor voltage divider network of pulse transformer in oil tank. In consideration of high precision but low sampling A/D, on the one hand, one or two points of pulse is applied as characteristic value. On the other hand, one dedicated peak sampling-holding circuit is designed to prolong and extend the sampling point to about 1ms duration so that multiple datum could be acquired and disposed within one repetition period.

For one or two points sampling, FPGA system is equipped with one sampling synchronous signal. Thus FPGA system could delay a certain time-span to match the interesting and appropriated sampling points (Fig-

ure 4), where the klystron is exactly excited by the pulse modulator. For multiple points sampling, FPGA system uses the averaged




Figure 4: Sampling point of pulse waveform.

value as featured value, but delay modulation is carried out by the hardware.

The final control result is showed in Figure 5, and the pulse-to-pulse amplitude stability is 0.03%(rms).




Figure 5: Pulse-to-pulse amplitude stability test result.

Pulse Waveform Sampling (Route B)

In route C, although the resolution meets control requirement well, but the sampling points are not sufficient to represent the characteristic value of the pulse waveform. In the mean time, multiple sampling of route C has no apparent difference from one or two points sampling because of sampling extension. Thus, in order to acquire directly a variety of datum within one pulse period, high sampling A/D is put forward and applied [4]. The test result is showed in Figure 6, and stability is also about 0.03%(rms).




Figure 6: Stability test result of route B.

HIGH STABLE CCPS DESIGN

Three different feedback control methods are discussed particularly in the above text, and the test results don't achieve the expected goal.

- [3] Y. Liu, M. Gu, Q. Yuan, L. Wang, “Designing signal conditioning circuit for stability control system of LINAC modula-tor”, nuclear technology, 2013, vol . 36, issue 3.
doi:http://ir.sinap.ac.cn/handle/331007/13523
- [4] L. Wang, M. Gu, Q. Yuan, “Data acquisition and processing in stability control system of LINAC modulator”, nuclear technology, 2012, 35(7).
doi:http://ir.sinap.ac.cn/handle/331007/12774